

 **ITALIANA**[®]
f e r r a m e n t a



K Lock



PUSH
CATCHES
AND
MAGNETIC
CATCHES



SYMBOLS AND FINISHES LEGEND

SYMBOLS



= SHELF SAFELY LOCKED DURING TRANSPORTATION AND AT HOME.



= ANTI-TURNOVER LOCKING SYSTEM



= NORMS / PATENTS



= PHILLIPS / POZIDRIV



= WITH BUFFER



= PART NO.



= BLADE SLOT



= WITH MAGNET



= PCS. PER PACKAGE



= COMBI SLOT



= HEXAGONAL SOCKET



= NEWTON



= CAPACITY LOADING



= HEXALOBULAR SOCKET



= FRICTION



= WOOD / GLASS THICKNESS



= COUNTERSUNK HEAD



= AUTOMATIC



= HOLE DIAMETER



= PAN HEAD



= DROP DOWN



= DIAMETER



= FLANGE HEAD



= LENGTH



= FLAT HEAD



= STANDARD HINGE



= HEIGHT



= TRILOBULAR SCREW



= KIMANA HINGE



= RIGHT VERSION



= SELF-TAPPING SCREW



= FLAP HINGE



= LEFT VERSION



= EURO THREAD



= WITH SPRING



= SETTING CODE



= METRIC THREAD



= WITHOUT SPRING



= PCS. PER PAD



= PRE-INSERTED SCREW



= REVERSED SPRING



= CUT ON REQUEST



= PRE-INSERTED SCREW AND SPREADING BUSH



= SELF ADHESIVE



= WITH FLANGE

NOTE: Printing errors and omissions may exist despite our best efforts to ensure accuracy. We reserve the right to alter specifications without notice.

MATERIALS

ZA = Zinc Alloy

ST = Steel

HSS = High Speed Steel

BR = Brass

ABS = Acrylonitrile Butadiene Styrene

ZAnk = Nickel-plated Zinc Alloy

STzk = Zinc-plated Steel

AL = Aluminium

WD = Wood

EVA = Ethylene Vinyl Acetate

EP = **ENGINEERING PLASTIC**

+ **EP** = other engineering plastic available on request

SR = **SOFT RUBBER**

+ **SR** = other soft rubber available on request

EPn = Natural Engineering Plastic

EPc = Clear Engineering Plastic

SRn = Natural Soft Rubber

EPw = White Engineering Plastic

EPg = Grey Engineering Plastic

SRw = White Soft Rubber

EPwg = Water Green Engineering Plastic

SRb = Black Soft Rubber



FINISHES



= OTHER FINISHES AVAILABLE ON REQUEST


PART NO.	FINISHES	PART NO.	FINISHES	PART NO.	FINISHES
00	Insignificant finish	IF	Middle Grey	UT	T-Met 9007
AA	Natural	IJ	Light Grey	UZ	T-Met
AB	White	IL	Grey 20	WA	Bronzed
AE	White 9010	IN	Grey met. 26	WI	Burnished
EA	Black	JB	Bright Aluminium	XD	Satin-finished Steel
EC	Matt Black	JC	Aluminium - Chrome	YA	Nickel-plated
EE	Anthracite	JD	Matt Aluminium	YB	Bright Nickel-plated
EW	Grey 9007	JE	Satin-finished Aluminium	YC	Matt Nickel-plated
FU	Gunmetal	JF	Aluminium - Brass	YD	Satin-finished Nickel-plated
FV	Gunmetal V52	JG	Aluminium 5	YQ	Black Nickel
GR	Raw	JL	Aluminium PE 11	Z9	Black Zinc
HA	Brass-Plated	JM	Aluminium RAL 9006	ZA	Zinc alloy
HH	Tropicalized	KA	Chrome	ZN	Zinc-plated
HL	Raw Brass	KB	Bright Chrome	ZQ	Bright Gold
HX	Graphite	KC	Matt Chrome	ZY	Titanium
IA	Grey	NN	Metallic Beige	ZZ	Clear
IB	Metallic Grey	RO	Red		



K LOCK


K LOCK is a magnetic system to safely keep the door closed.
Suitable for unsprung or Flap/Piano hinges, K LOCK can be either embedded into the panel through a \varnothing 10 mm hole, or installed visible, fixed with adapter housing
K LOCK is available in three colors: white, anthracite and light grey.
A 3,5 mm adjustment can be carried out by using a 1,2x6,5 mm blade screwdriver.

INSTALLATION THROUGH ADAPTER HOUSING




recommended countersunk head wood screws \varnothing 3,5 x16 mm

ADJUSTMENT




For details refer to "K PUSH TECH AND K LOCK DOOR PLATES".

INSTALLATION TO BE EMBEDDED INSIDE THE PANEL




ATTENTION:
In case glue is added, make sure the quantity is carefully dosed, so that it doesn't reach the inner part of the mechanism, thus blocking the adjustment.

ADJUSTMENT



For details refer to "K PUSH TECH AND K LOCK DOOR PLATES".







 = 100 pcs.




55007010EE
55007010IJ
55007010AB






 = 100 pcs.




57015020EE
57015020IJ
57015020AB





 = Ø 3 mm


 = 100 pcs.





57015040EE
57015040IJ
57015040AB




		= Ø 5 mm	= 100 pcs.
57015060EE			
57015060IJ			
57015060AB			

FIXING ACCESSORY FOR K LOCK ADAPTER PLATES PART NO. 57015040



	= Ø 3 mm		
			= 10.000 pcs.
60101390ZN			


FIXING ACCESSORY FOR K LOCK ADAPTER PLATES PART NO. 57015060



	= Ø 5 mm		
			= 5000 pcs.
60501050YA			




K PUSH TECH AND K LOCK DOOR PLATES




= Ø 3 mm
 = Ø 3 mm
 = 100 pcs.

123
55006160XD




= Ø 3 mm
 = Ø 3 mm
 = 100 pcs.

123
55006030YA




= Ø 3 mm = PZ2 = PZ2
 = Ø 3 mm
 = Ø 3 mm
 = 100 pcs.

123
55006100YA




= Ø 5 mm
 = Ø 5 mm
 = 100 pcs.

123
55006040YA



= Ø 6 mm
 = Ø 6 mm
 = 100 pcs.


123
55006070YA



= Ø 8 mm

ST = 100 pcs.


55006050YA



= Ø 2,5 mm

ST = 100 pcs.


55006120YA



= Ø 2,5 mm

ST = 100 pcs.

55006170YA




= Ø 6 mm

ST = 100 pcs.

55006130YA





ACCESSORY FOR PART NO. 55006130YA AND 55006120YA




	= Ø 2,5 mm	
ST		
60201140YA		

PLATE FOR K PUSH WITH ADAPTER HOUSING FOR CURVED DOORS




	= Ø 3 mm	
ST		
55006110YA		

ACCESSORY FOR PART.NO 55006110YA



	= Ø 3 mm	
ST		
60103140YA		



www.italianaferramenta.com